



# SEALTEK

## ADVANCED COATING TECHNOLOGIES

44 Sophia Street, Fairlands, Johannesburg  
 P.O. BOX 731 074, Fairlands 2030, South Africa  
 TELEPHONE: + 27 10 594 - 4726  
 E-mail: info@sealtek.co.za  
 Reg no: 2015/358427/07

### AQUATINT

AquaTint is a **Polymeric** additive mixture that has excellent saturation levels that enhances the stability of the substrate. AquaTint is our colour boosted primer to be applied before any of our paint and waterproofing products. It also repels water from the substrate. This makes for the ideal finish on a slab where you want a colour finish over our PolyScreed or as a primer on walls and roofs before applying your desired paint colour. Used on a variety of substrates, such as concrete, walls, plaster, tiles, etc.

AquaTint	<ul style="list-style-type: none"> <li>• 20ltr and 5ltr</li> <li>• Used as a colour primer on cementitious substrates before another paint or waterproof coating is applied.</li> <li>• Can be used as a finished coating over our screeds.</li> </ul>
Practical Coverage	<ul style="list-style-type: none"> <li>• 100 – 120 m<sup>2</sup> per 20ltr @ 1 coat application substrate dependent.</li> <li>• To be applied to cementitious substrates only.</li> </ul>
Cleaning	<ul style="list-style-type: none"> <li>• AquaTint is water based therefore paint and application tools can be cleaned off with water.</li> </ul>
Surface Preparation	<ul style="list-style-type: none"> <li>• Remove all existing coatings.</li> <li>• Ensure to remove any dust, debris, salt, algae, fungi or chemicals that may cause adhesion difficulties to the substrate.</li> <li>• Ensure that the substrate is completely dry before application of the product – less than 10% moisture.</li> </ul>
Method of Application	<ul style="list-style-type: none"> <li>• Surface application temperature 5-35 degrees Celsius.</li> <li>• Once the surface area has been prepared as above on cementitious substrates only a single coat of AquaTint is to be applied.</li> <li>• After the AquaTint has dried - approximately an hour the paint or waterproof coating can be applied.</li> <li>• AquaTint can be applied with brush, roller or spray on application.</li> <li>• On a completed screed a 1 coat application can be painted on for an opaque colour finish.</li> </ul>
Drying Time	<ul style="list-style-type: none"> <li>• Touch Dry or recoating – 1-2 Hours at ± 25 °C</li> <li>• Fully Cured - 7 Days at ± 25 °C</li> </ul>
Colours	<ul style="list-style-type: none"> <li>• Depend on the colour chosen, we have a variety of 90 standard</li> </ul>
Advantages of AquaTint	<ul style="list-style-type: none"> <li>• Eco Friendly</li> <li>• Seamless</li> <li>• Ease of application - Brush, Roll, Spray on</li> <li>• Low to no maintenance</li> <li>• Flexible</li> </ul>