



# SEALTEK

## ADVANCED COATING TECHNOLOGIES

44 Sophia Street, Fairlands, Johannesburg  
 P.O. BOX 731 074, Fairlands 2030, South Africa  
 TELEPHONE: + 27 10 594 - 4726  
 E-mail: info@sealtek.co.za  
 Reg no: 2015/358427/07

### DAMP-END

Damp-End is a two-part system consisting of dry and wet ingredients that get mixed together. Damp-End is a plasticized cementitious system. All the binders and materials that Damp-End comprises of is eco-friendly.

Damp-End	<ul style="list-style-type: none"> <li>• Damp-End is pre-packaged.</li> <li>• 20ltr bucket wet mix.</li> <li>• A bag of pre-mixed dry ingredients</li> </ul>
Practical Coverage	<ul style="list-style-type: none"> <li>• 15-30m<sup>2</sup> per 23kg pack at 2-3coats</li> </ul>
Cleaning	<ul style="list-style-type: none"> <li>• Clean the Brushes immediately after use, with water, as it will be very difficult to clean once the mixture has dried.</li> </ul>
Surface Preparation	<ul style="list-style-type: none"> <li>• Ensure to remove any dust, debris, salt, algae, fungi or chemicals that may cause adhesion difficulties to the substrate.</li> <li>• Ensure that the substrate has dried properly before any application of the product.</li> </ul>
Method of Application	<ul style="list-style-type: none"> <li>• Open the bucket of wet mix and gradually add the dry mix to the wet mix while continuously turning over the mixture.</li> <li>• Block Brush / Roller application             <ul style="list-style-type: none"> <li>- Once the 1<sup>st</sup> coat has been applied the surface must be touch dry before the 2<sup>nd</sup> and 3<sup>rd</sup> coat is applied.</li> </ul> </li> <li>• After final coat the area needs to cure for 2 hours.</li> </ul>
Drying Time	<ul style="list-style-type: none"> <li>• Touch dry or recoating – 1-2 Hours at ± 25 °C</li> </ul>
Colours	<ul style="list-style-type: none"> <li>• The Damp-End is a cement grey.</li> </ul>
Product Data: VOC: Flashpoint Solid Content Characteristics Eye Contact Inhalation Ingestion Skin Contact Toxicology	<ul style="list-style-type: none"> <li>• Low VOC's &lt; 1%</li> <li>• Non-Flammable</li> <li>• &gt;75%</li> <li>• Flexible</li> <li>• Exceptional Adhesion Properties</li> <li>• If in eyes wash out immediately with water. Might cause eye irritation as a precaution seek medical advice</li> <li>• No harmful effect expected, do remove victim to a well-ventilated area as precaution.</li> <li>• Rinse mouth with water, seek medical advice.</li> <li>• Skin might feel dry if in contact for long duration of time.</li> <li>• This product has low Toxicity, material has been classified as non-hazardous</li> </ul>